

Markerboard Material Comparison

	CeramicSteel	Glassboards	Whiteboard Paint	Painted Steel	Melamine
Materiality	 Porcelain enamel fused to steel at 800°C / 1500°F 	Tempered glass surfaceLack of clarity/visibility due to extreme high gloss	High gloss paintTypically a two-component epoxy paint	High gloss polymer paint over a steel substrate	Plastic resin, high pressure laminate adhered to a substrate
Durability	 Resistant to bacteria, chemicals, fire and scratching Withstands high-traffic areas and heavy use 	Resistant to scratchingShatters under impact	Only as hard as the wall it is painted on and easily sustains damageWears away with extended or heavy use	Easily scratchesErasable surface wears away with use	Resists scratches better than paint, but will easily dentDry erase surface quality diminishes with use
Dry Erase Performance	 Never stains or ghosts Easily withstands permanent marker 3x better initial erasability 10x better erasability after aging Smooth surface without friction 	 Never stains or ghosts Withstands permanent marker Good erasability Maintains erasability after aging Smooth surface 	 Stains and ghosts easily Does not withstand permanent marker Does not maintain dry erase quality with aging Inconsistent texture 	 Stains and ghosts easily No permanent marker Low initial erasability Significant reduction in erasability with aging Smooth surface 	 Stains and ghosts easily No permanent marker Low initial erasability Significant reduction in erasability with aging Smooth surface
Versatility + Design Flexibility	 Inherently magnetic, does not require special magnets Designed for style and customization Offers a wide selection of colors and custom image/design printing Floor-to-ceiling options and sizes 	 Sometimes magnetic at additional cost, typically requires rare earth magnets High level of design Wide color selection Variety of sizes 	 Magnetic primer option at additional cost that only retains rare earth magnets that cost approximately \$15 each Flexible design capacity Four color options, must use clear for colored or design backgrounds 	Always magneticStandard whiteboard formatOffers a variety of solid color options	 Magnetic options available at additional cost Standard whiteboard format Offers a variety of colors, patterns and printing options
Environmental Impact	Cradle-to-Cradle Certified BronzeIndoor Advantage Gold certification90% recyclable	Low environmental impact	High odor emissionsEmpty paint canisters go to landfillsSome products are green certified after curing	Some components are recyclableSustainably-sourced steel is dependent upon individual manufacturers	High environmental impactLaminate surfaces are not environmentally sustainable
Longevity	Lifetime warrantyLasts for 50+ yearsWill never require replacement	Limited warrantiesLasts for 50 years when it doesn't shatter	Limited warrantiesLasts for 2-5 yearsRequires frequent re-application	Limited warrantiesLasts 2-5 years	Limited warrantiesLasts 2-5 years
Installation	 As straightforward as hanging a framed photograph Takes minutes to install, more lightweight Can be field-cut for outlets or light switches 	 Installation is relatively straightforward Takes longer to install, glassboards are heavier and less durable Cannot be field-cut for outlets or light switches 	 Requires mixing, curing, proper ventilation and multiple coats Takes over seven days to cure 	Basic installationInstallation hardware is not always included	Basic installation
Customer Service	Consistent customer service personnel at individual dealer locations	 Call center customer service lines Individual sales representatives Online sales Must ship vertically 	Sold in retail stores and onlineUnresponsive call lines	Can be found in retail stores and online	Can be found in retail stores and online

©2025 Polyvision Corporation. All rights reserved. Trademarks used herein are the trademarks of Polyvision Corporation or of their respective owner.

polyvision.com